

smiths medical

pneupac™



paraPAC plus™ Transport Ventilator

PNEUPAC®
Ventilation in Motion

MRI TESTED

For use in a spatial gradient of up to 7.5 Tesla/m. For full details, please refer to the Instructions for Use.



嘉榮醫療有限公司
GOODWIN health care Ltd.

Tel: (852) 2408 8838
Fax: (852) 2408 1329
Email: hksales@goodwin.com.hk
Website: www.goodwin.com.hk



PARAPAC PLUS™ TRANSPORT VENTILATOR

The paraPAC plus™ gives you the versatility to deliver mechanical ventilation, demand and free flow oxygen therapy and CPAP all from one compact, lightweight unit.

The paraPAC plus™ is designed for use in a wide range of environments. This includes the use in hospitals and in more demanding locations such as ambulances, aircraft, outdoors, and in MRI scanners.

The paraPAC plus™ is the latest addition to the Pneupac® range, offering the reliability you expect, plus:

- Use in MRI scanner to 3 Tesla
- Built in oxygen therapy facility
- CPAP and integrated PEEP function
- DEMAND system, allowing the patient to breathe with the ventilator
- Lightweight and rugged
- Manual breath with Pneupac® patented volume limiter
- Fits to existing Pneupac® brackets
- Luminescent manometer
- Display of inspiratory and expiratory pressure
- Hyperinflation accessory for neonatal ventilation



paraPAC plus™ Technical Data:

Weight 2.4kg (5.3lb), Measurements 240 x 165 x 93mm (9.25 x 6.5 x 3.7in), Tidal Volume 70-1500ml, Frequency: 8-40bpm, I:E ratio 1:2, FiO₂: 50% and 100%, Pressure relief valve and alarm: 20-60cmH₂O, Power source Medical Oxygen 280-600kPa, Patient circuit 1.5m long, PEEP range 0-20cmH₂O, Oxygen Flow range 0-35L/min (model 310 only), CPAP: up to max of 10-16cm H₂O at 35L/min flow (depending on patient condition)

MR Conditional:

3 Tesla field strength, 7.5 Tesla/m (750g/cm) spatial gradient, Open bore shielded magnet


Alarms:

High pressure, Low pressure (disconnect), Low battery, Low supply gas

Battery for alarms:

3.6V Lithium ion battery. Battery lifetime > 1 year

ORDER INFORMATION: All models are suitable for use in MRI scanners	
Item Code	Description
P310NGB	paraPAC plus™ with PEEP, CPAP and manual control
100/905/340	Single-limb patient circuit without PEEP valve
100/905/360	CPAP circuit with medium mask
100/905/361	CPAP circuit with large mask
P300NGB	paraPAC plus™ with manual control
100/905/341	Single-limb patient circuit with PEEP valve



PRODUCT(S) DESCRIBED MAY NOT BE LICENSED OR AVAILABLE FOR SALE IN CANADA AND OTHER COUNTRIES

Smiths Medical International Ltd.
1500 Eureka Park, Lower Pemberton
Ashford, Kent, TN25 4BF
Tel: +44 (0)845 850 0445
pneupac@smiths-medical.com
www.smiths-medical.com

Smiths Medical ASD, Inc.
6000 Nathan Lane North
Minneapolis, MN 55442, USA
Tel: 1-614-210-7300
Toll-Free USA: 1-800-258-5361
www.smiths-medical.com



嘉榮醫療有限公司
GOODWIN health care Ltd.

MLUTCA-1029
CE
2797
smiths medical



Find your local contact information at: www.smiths-medical.com/customer-support

Smiths Medical is part of the global technology business Smiths Group plc. Please see the Instructions for Use/Operator's Manual for a complete listing of the indications, contraindications, warnings and precautions. paraPac, Pneupac and the Smiths Medical design mark are trademarks of Smiths Medical. The symbol © indicates the trademark is registered in the U.S. Patent and Trademark Office and certain other countries. All other names and marks mentioned are the trademarks or service marks of their respective owners. ©2019 Smiths Medical. All rights reserved. TV195629GB-112019